

reet nome ; Stand	, the population of the party o
Membership Public	ations/Services Standards Conferences Careers/Jobs
المجال المحال	Welcome United States Patent and Trademark Of
Help FAQ Terms IB Review	EEE Paer Quick Links ▼
Welcome to IEEE Xplore* - Home - What Can I Access? - Log-out	Your search matched 76 of 815706 documents. Results are shown 15 to a page, sorted by Relevance in descending order. You may refine your search by editing the current search expression or entering a new one the text Then click Search Again . circuit <and> simulation <and> transient <and> nonlinear <and> current</and></and></and></and>
Tables of Contents	Search Again
O- Journals & Magazines O- Conference	Results: Journal or Magazine = JNL Conference = CNF Standard = STD
Proceedings - Standards	16 Sampled data simulation of linear and nonlinear circuits Opal, A.;
Search	Computer-Aided Design of Integrated Circuits and Systems, IEEE Transactions of Volume: 15 Issue: 3, Mar 1996 Page(s): 295 -307
Member Services	[Abstract] [PDF Full-Text (1184 KB)] IEEE JRN
O- Join IEEE O- Establish IEEE Web Account	17 Analysis of switched-capacitor and switched-current networks with complete settling assumption Suyama, K.; Yustin, I.;
O- Access the IEEE Member Digital Library	Circuits and Systems, 1996. ISCAS '96., 'Connecting the World'., 1996 IEEE International Symposium on , Volume: 4 , 12-15 May 1996 Page(s): 428 -431 vol.4
Print Format	

[Abstract] [PDF Full-Text (336 KB)] IEEE CNF

18 A rapidly convergent technique for determining the response of AC/D converters

Naidu, S.R.; Trindade, W.J.;

Harmonics And Quality of Power, 1998. Proceedings. 8th International Conferen

Volume: 2 , 14-18 Oct 1998 Page(s): 958 -963 vol.2

[Abstract] [PDF Full-Text (316 KB)] IEEE CNF

19 Analogue implementation of a neural network controller for UPS inveapplications

Chow, M.H.L.; Dehong Xu; Leung, F.H.F.; Xiao Sun; Yim-Shu Lee; Yousheng Wa Power Electronics, IEEE Transactions on , Volume: 17 Issue: 3, May 2002

[Abstract] [PDF Full-Text (361 KB)] IEEE JRN

20 Duomode non-linear state space averaged SPICE model of a current m buck converter

Chen, J.E.; Rodriguez, F.D.;

Applied Power Electronics Conference and Exposition, 1988. APEC '88. Conferen

Proceedings 1988., Third Annual IEEE, 1-5 Feb 1988

Page(s): 53 -58

[Abstract] [PDF Full-Text (300 KB)] IEEE CNF

21 Simulation of current-mode quasi-resonant converters in full wave re switch configuration

Costiner, S.; Ioinovici, A.;

Circuits and Systems, 1990., Proceedings of the 33rd Midwest Symposium on , 1

Aug 1990

Page(s): 1098 -1101 vol.2

[Abstract] [PDF Full-Text (240 KB)] IEEE CNF

22 Control of front-end three-phase boost rectifier

Boroyevich, D.; Hiti, S.;

Applied Power Electronics Conference and Exposition, 1994. APEC '94. Conferen

Proceedings 1994., Ninth Annual, 13-17 Feb 1994

Page(s): 927 -933 vol.2

[Abstract] [PDF Full-Text (464 KB)] IEEE CNF

23 Accurate modelling of the non-linear settling behaviour of current me circuits

Kaiser, A.; Moeneclaey, N.;

Circuits and Systems, 1994. ISCAS '94., 1994 IEEE International Symposium on

Volume: 1, 30 May-2 Jun 1994

Page(s): 339 -342 vol.1

[Abstract] [PDF Full-Text (276 KB)] IEEE CNF

24 Comparison of fuzzy logic and current-mode control techniques in bu boost and buck/boost converters

Fang Hsien Wang; Lee, C.Q.;

Power Electronics Specialists Conference, 1995. PESC '95 Record., 26th Annual

Volume: 2, 18-22 Jun 1995 Page(s): 1079 -1085 vol.2

25 PWM AC/DC converter with reduced sampling frequency fuzzy contro

Bogdan, I.; Pastravanu, A.; Popescu, G.S.;

Industrial Electronics, 1997. ISIE '97., Proceedings of the IEEE International

Symposium on , 7-11 Jul 1997

Page(s): 1228 -1231 vol.3

[Abstract] [PDF Full-Text (328 KB)] IEEE CNF

26 Simulator for switched-current integrated circuits

Ionis, G.; Suyama, K.; Yusim, I.;

Custom Integrated Circuits Conference, 1998., Proceedings of the IEEE 1998, 1

May 1998

Page(s): 459 -462

[Abstract] [PDF Full-Text (340 KB)] IEEE CNF

27 Simulation of electric power circuit breakers in the EMTP incorporatin electric arc models: application to reactor bank switching and short line

Calva, P.A.; Ramirez, C.;

Electrical Insulation and Dielectric Phenomena, 2001 Annual Report. Conference 2001

Page(s): 660 -664

[Abstract] [PDF Full-Text (324 KB)] IEEE CNF

28 Topology based magnetic model for steady-state and transient studie three-phase core type transformers

Brierley, R.H.; Narang, A.;

Power Systems, IEEE Transactions on , Volume: 9 Issue: 3 , Aug 1994

Page(s): 1337 -1349

[Abstract] [PDF Full-Text (1164 KB)] IEEE JRN

29 The simulation of circuit breaker switching using a composite Cassie-modified Mayr model

Christopoulos, C.; Howe, A.F.; Pereira, E.T.; Thomas, D.W.P.;

Power Delivery, IEEE Transactions on , Volume: 10 Issue: 4 , Oct 1995

Page(s): 1829 -1835

[Abstract] [PDF Full-Text (556 KB)] IEEE JRN

30 Simulation of dynamics of electromagnetic driving device for comet g





Magnetics, IEEE Transactions on , Volume: 34 Issue: 5 , Sep 1998

Page(s): 3146 -3149

[Abstract] [PDF Full-Text (424 KB)] IEEE JRN

[Prev] 1 2 3 4 5 6 [Next]

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account | New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online Publications | Help | FAQ | Terms | Back to Top

Copyright © 2002 IEEE — All rights reserved

			ı	
L Number	Hits	Search Text	DB	Time stamp
1	1093	discontinu\$5 near2 impedance	USPAT;	2002/12/20
-		•	US-PGPUB;	16:41
			IBM TDB	
2	4	(simulat\$4 and circuit).ab. and	USPAT;	2002/12/20
2	1 -	(discontinu\$5 near2 impedance)	US-PGPUB;	17:08
		(discontinus) hearz impedance)	1	17.00
		#5726702#	IBM_TDB	2002/12/20
3	6	"5736783"	USPAT;	2002/12/20
			US-PGPUB;	17:08
			IBM_TDB	
-	13941	usami.in. or kobayashi.in.	USPAT;	2002/12/20
			US-PGPUB	11:33
-	4	(usami.in. or kobayashi.in.) and "TOSHIBA	USPAT;	2002/12/20
		TEC KABUSHIKI KAISHA".as.	US-PGPUB	11:33
_	403	"TOSHIBA TEC KABUSHIKI KAISHA".as.	USPAT;	2002/12/20
			US-PGPUB	11:35
l <u>-</u>	492585	simulat\$4 or model\$3 or emulat\$4	USPAT;	2002/12/20
			US-PGPUB	11:40
_	16	"TOSHIBA TEC KABUSHIKI KAISHA".as. and	USPAT;	2002/12/20
1	"	(simulat\$4 or model\$3 or emulat\$4)	US-PGPUB	11:36
_	169333	(simulat\$4 or model\$3 or emulat\$4) and	USPAT;	2002/12/20
-	10222	1 ,	•	
		circuit	US-PGPUB;	11:41
			IBM_TDB	/ /
-	60026	((simulat\$4 or model\$3 or emulat\$4) and	USPAT;	2002/12/20
		circuit) and volt\$4 and current and	US-PGPUB;	11:43
		(resist\$4 or conduct\$4)	IBM_TDB	
-	53287	(((simulat\$4 or model\$3 or emulat\$4) and	USPAT;	2002/12/20
		circuit) and volt\$4 and current and	US-PGPUB;	11:46
		(resist\$4 or conduct\$4)) and (line\$5 or	IBM TDB	
		nonline\$5 or non-lin\$5)	_	
_	50248	((((simulat\$4 or model\$3 or emulat\$4) and	USPAT;	2002/12/20
		circuit) and volt\$4 and current and	US-PGPUB;	11:51
		(resist\$4 or conduct\$4)) and (line\$5 or	IBM TDB	
		nonline\$5 or non-lin\$5)) and (time or	1511_155	ļ
		timing)		·
	286196		HCDAM.	2002/12/20
_	286196	1 1 1	USPAT;	
		intersect\$4))	US-PGPUB;	11:51
			IBM_TDB	0000 (10 (00
-	14867	((((simulat\$4 or model\$3 or emulat\$4) and	USPAT;	2002/12/20
	į	circuit) and volt\$4 and current and	US-PGPUB;	12:20
		(resist\$4 or conduct\$4)) and (line\$5 or	IBM_TDB	[
		nonline\$5 or non-lin\$5)) and (time or		
		timing) and (((wire or wiring) same		
		(connect\$4 or intersect\$4)))		
-	3948		USPAT;	2002/12/20
		and circuit) and volt\$4 and current and	US-PGPUB;	12:02
	1	(resist\$4 or conduct\$4)) and (line\$5 or	IBM TDB	_
		nonline\$5 or non-lin\$5)) and (time or		
	!	timing) and (((wire or wiring) same		<u> </u>
		(connect\$4 or intersect\$4)))) and	[
1		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		[
	1 2242	(electron or particle)	HCDAM:	2002/12/20
-	3249	((((((simulat\$4 or model\$3 or emulat\$4)	USPAT;	2002/12/20
		and circuit) and volt\$4 and current and	US-PGPUB;	12:03
		(resist\$4 or conduct\$4)) and (line\$5 or	IBM_TDB	
		nonline\$5 or non-lin\$5)) and (time or	1	
		timing) and (((wire or wiring) same		
	l	(connect\$4 or intersect\$4)))) and	1	
		(electron or particle)) and state	1	
-	2112		USPAT;	2002/12/20
		and circuit) and volt\$4 and current and	US-PGPUB;	12:03
[(resist\$4 or conduct\$4)) and (line\$5 or	IBM TDB	
		nonline\$5 or non-lin\$5)) and (time or		
		timing) and (((wire or wiring) same	1	
		(connect\$4 or intersect\$4)))) and		
		(electron or particle)) and state) and	1	1
	1	transfer\$5	İ	

Search History 12/20/02 5:31:12 PM

-	1727	(((x,((simulat\$4 or model\$3 or emulat\$.,		2002/12/20
		and circuit) and volt\$4 and current and	US-PGPUB;	12:04
		(resist\$4 or conduct\$4)) and (line\$5 or	IBM_TDB	
		nonline\$5 or non-lin\$5)) and (time or		
		timing) and (((wire or wiring) same	i	
		(connect\$4 or intersect\$4)))) and (electron or particle)) and state) and		
		transfer\$5) and (rule or law or guide or		
		standard)		
_	1578	(((((((simulat\$4 or model\$3 or	USPAT;	2002/12/20
		emulat\$4) and circuit) and volt\$4 and	US-PGPUB;	12:05
İ		current and (resist\$4 or conduct\$4)) and	IBM_TDB	
		(line\$5 or nonline\$5 or non-lin\$5)) and	_	
		(time or timing) and (((wire or wiring)		
		same (connect\$4 or intersect\$4)))) and		
		(electron or particle)) and state) and		
		transfer\$5) and (rule or law or guide or		
	1250	standard)) and source	HCDAT.	2002/12/20
_	1259	<pre>((((((((((simulat\$4 or model\$3 or emulat\$4) and circuit) and volt\$4 and</pre>	USPAT; US-PGPUB;	2002/12/20 12:08
		current and (resist\$4 or conduct\$4)) and	IBM TDB	12.00
		(line\$5 or nonline\$5 or non-lin\$5)) and	1271_122	
		(time or timing) and (((wire or wiring)		
	1	same (connect\$4 or intersect\$4)))) and		
		(electron or particle)) and state) and		
	[i	transfer\$5) and (rule or law or guide or		
		standard)) and source) and (computer or		
		cpu or processor or microprocessor)		
-	1210	((((((((((simulat\$4 or model\$3 or	USPAT;	2002/12/20
		emulat\$4) and circuit) and volt\$4 and	US-PGPUB;	12:13
		current and (resist\$4 or conduct\$4)) and (line\$5 or nonline\$5 or non-lin\$5)) and	IBM_TDB	
		(time or timing) and (((wire or wiring)		
		same (connect\$4 or intersect\$4)))) and		
		(electron or particle)) and state) and		
		transfer\$5) and (rule or law or guide or		
		standard)) and source) and (computer or		
		cpu or processor or microprocessor)) and		
		(unit or cell or node)		22224242
-	2406	(simulat\$4 and circuit).ab.	USPAT;	2002/12/20
	1		US-PGPUB;	16:42
	0	(((((((((((simulat\$4 or model\$3 or	<pre>IBM_TDB USPAT;</pre>	2002/12/20
-		emulat\$4) and circuit) and volt\$4 and	US-PGPUB;	12:14
	1	current and (resist\$4 or conduct\$4)) and	IBM TDB	
		(line\$5 or nonline\$5 or non-lin\$5)) and		
	}	(time or timing) and (((wire or wiring)		
		same (connect\$4 or intersect\$4)))) and		
		(electron or particle)) and state) and		
	1	transfer\$5) and (rule or law or guide or		
		standard)) and source) and (computer or		
		cpu or processor or microprocessor)) and		
		(unit or cell or node)) and ((simulat\$4		
_	2142	<pre>and circuit).ab.) ((simulat\$4 and circuit).ab.) and (volt\$4</pre>	USPAT;	2002/12/20
-	2142	or current or (resist\$4 or conduct\$5 or	USPAT; US-PGPUB;	12:19
		imped\$4))	IBM TDB	12.17
_	1049	((simulat\$4 and circuit).ab.) and (volt\$4	USPAT;	2002/12/20
	10.5	and current and (resist\$4 or conduct\$5 or	US-PGPUB;	12:19
		imped\$4))	IBM TDB	
_	385	(((simulat\$4 and circuit).ab.) and	USPAT;	2002/12/20
		(volt\$4 and current and (resist\$4 or	US-PGPUB;	12:19
		conduct\$5 or imped\$4))) and transfer\$5	IBM_TDB	
-	303	((((simulat\$4 and circuit).ab.) and	USPAT;	2002/12/20
		(volt\$4 and current and (resist\$4 or	US-PGPUB;	12:20
	1	conduct\$5 or imped\$4))) and transfer\$5)	IBM_TDB	
		and state	1	1

_	141	((((USPAT;	2002/12/20
		<pre>(volt\$4 and current and (resist\$4 or conduct\$5 or imped\$4))) and transfer\$5)</pre>	US-PGPUB; IBM_TDB	12:21
		<pre>and state) and (linear\$3 or nonlinear\$3 or non-linear\$3)</pre>		
_	140	<pre>((((((simulat\$4 and circuit).ab.) and (volt\$4 and current and (resist\$4 or conduct\$5 or imped\$4))) and transfer\$5)</pre>	USPAT; US-PGPUB; IBM_TDB	2002/12/20
		<pre>and state) and (linear\$3 or nonlinear\$3 or non-linear\$3)) and (time or timing)</pre>		